JOSTAG cable laying technology

CABLE COIL TRAILER KSA 3500/5000/6000



Cable coil trailer, load capacity 4000 kg

This trailer is designed for a load capacity of up to 4t. The diameter of the cable coils is 1m to 3m; the width 0.6m to 1.7m.

Safe 1-man operation with hydraulic coil loading, hydraulic friction drive in both directions, and wire or wireless remote control.

Double axles guarantees optimal stability and handling in rough terrain. The maximum road speed is 80 km/h.

The welaki loading system is also suitable for transporting troughs, which can be emptied with a tipping device.

Technical data KSA 3500 B

Length: 4500 mm Width: $2280\,\text{mm}$ Loading width: 1500 mm Max. reel width: 1425 mm Max. reel diameter: 3000 mm Total weight: 3500 kg Load capacity: 2250 kg Drawbar load: 150 kg

Technical data KSA 5000 B

5200 mm Length: 2300 mm Width: Loading width: 1500 mm Max. reel width: 1425 mm Max. reel diameter: 3000 mm 5000 kg Total weight: Load capacity: 3500 kg Drawbar load: 150 kg

Technical data KSA 6000 B KSA 6000 S

5200 mm 5200 mm Length: 2300 mm Width: 2550 mm Loading width: 1725 mm 1500 mm Max. reel width: 1425 mm 1650 mm Max. reel diameter: 3100 mm 3100 mm Total weight: 6000 kg 6000 kg Load capacity: 4000 kg 4000 kg Drawbar load: 180 kg 180 kg

CABLE COIL TRAILER KSA 3500/5000/6000

Standard version

- · Vangard petrol engine 9.5 kW (13 HP) with battery and starter
- · Double axles for optimal stability and handling in rough terrain
- · Hydraulic coil loading
- Hydraulic support jacks
- Hydraulic coil drive (KSA 3500 / 5000 single, KSA 6000 double)
- Coil release and brake
- · Wire remote control
- Weight-optimized reel axle
- Height-adjustable drawbar, optionally with ball or ring system





Further options

- Diesel engine 7.3 kW (10 HP)
- · Particle filter
- · Electrical drive
- · Dual braking circuits (EURO norm) without ABS
- · Wireless remote control
- Pulling force measuring system with software and data logging card for force, distance and speed measurement with force limit cutout.
 Suitable for all coil types after key data input
- · Tarpaulin cover for the front part
- Diverse tipping or transport troughs





JOST AG

Cable laying technology

Obermattweg 25 CH-3550 Langnau i.E. Phone +41 (0)34 409 55 55 Fax +41 (0)34 409 55 66

www.jostag.ch info@jostag.ch