

Seilverbinder / Connecteur de câble / Jointing sleeve

Drallausgleichswirbel / Emerillon / Line swivel

Stahl verzinkt, passiviert, max. Bruchlast ohne Sicherheit /
Acier galvanisé, passivé, charge de rupture max. sans sécurité /
Galvanised steel, passivated, max. rupture charge without security



Art.-Nr.	Seil Ø Câble Ø Cable Ø	Gewicht (kg/Stk.) Poids (kg/pc) Weight (kg/pc)	Bruchlast (kN) Charge de rupture (kN) Rupture charge (kN)
60.17.1001	10	0.3	70
60.17.1002	13	1	110
60.17.1003	18	2.2	220

Drallausgleichswirbel / Emerillon / Line swivel

Stahl, max. Bruchlast mit 3-facher Sicherheit /
Acier, charge de rupture max. avec sécurité triple /
Steel, rupture charge max. with 3-fold security



Art.-Nr.	Seil Ø Câble Ø Cable Ø	Gewicht (kg/Stk.) Poids (kg/pc) Weight (kg/pc)	Bruchlast (kN) Charge de rupture (kN) Rupture charge (kN)
60.16.0002	6	0.85	5
60.16.0003	8	0.15	10
60.16.0004	10	0.25	15.6
60.16.0005	11	0.45	22.5
60.16.0006	12/13	0.62	31.5
60.16.0007	16	0.97	44.5

Schäkel / Manilles / Shackles

Geschweißte Form, feuerverzinkt, max. Bruchlast mit 5-facher Sicherheit /
 Forme échancrée zinguées, charge de rupture max. avec sécurité quintuple /
 Galvanised, rupture charge max. with 5-fold security



Art.-Nr.	Seil Ø Câble Ø Cable Ø	Inches	Gewicht (kg/Stk.) Poids (kg/pc) Weight (kg/pc)	Zulässige Zuladung (kN) Charge admissible (kN) Admissible charge (kN)
60.17.1004	12	1/4"	0.05	5
60.17.1005	16	3/8"	0.14	10
60.17.1006	18	7/16"	0.22	15
60.17.1007	21	1/2"	0.33	20
60.17.1008	27	5/8"	0.65	33
60.17.1009	32	3/4"	0.97	48

Schäkel / Manilles / Shackles

Geschmiedet, verzinkt, max. Bruchlast ohne Sicherheit /
 Forge zingué, charge de rupture max. sans sécurité /
 Forged galvanised, max. rupture charge without security



Art.-Nr.	Seil Ø Câble Ø Cable Ø	Gewicht (kg/Stk.) Poids (kg/pc) Weight (kg/pc)	Bruchlast (kN) Charge de rupture (kN) Rupture charge (kN)	Zulässige Zuladung (kN) Charge admissible (kN) Admissible charge (kN)
60.17.1010	10	0.135	70	12
60.17.1011	13	0.325	110	20